


Raccordi Femmina Sede JIC 74°
JIC Females 74° Cone
JIC 74° Dichtkegel

ISO 12151-5 (ISO 8434-2)

DKJ



	CODICE Part n° Bestell. nr.	Filetto Thread Gewinde	Ø F ø F ø F	DN Tubo ND Hose DN Schlauch	CH	L	Ø C	H	M
a	S 30 43 0 604 005 H	7/16" -20 UNF		3/16" 05	14	45,5	3	23,5	14
a	S 30 43 0 604 006 H	7/16" -20 UNF		1/4" 06	14	51,5	4	23,5	14
a	S 30 43 0 606 006 H	1/2" -20 UNF		1/4" 06	17	52,5	4	24,5	15
a	S 30 43 0 606 008 H	1/2" -20 UNF		5/16" 08	17	52,5	5,5	24,5	15
a	S 30 43 0 608 006 S	9/16" -18 UNF		1/4" 06	19	54,5	4	26,5	16,5
a	S 30 43 0 608 008	9/16" -18 UNF		5/16" 08	19	55	5,5	27	17
a	S 30 43 0 608 010	9/16" -18 UNF		3/8" 10	19	56	7	26,5	16,5
a	S 30 43 0 610 010	3/4" -16 UNF		3/8" 10	24	60	7	30,5	19
a	S 30 43 0 610 013 A	3/4" -16 UNF		1/2" 13	24	59,5	9,5	30	18,5
a	S 30 43 0 613 010 A	7/8" -14 UNF		3/8" 10	27	63	7	33,5	20
a	S 30 43 0 613 013 A	7/8" -14 UNF		1/2" 13	27	64,5	9,5	35	21
a	S 30 43 0 613 016 A	7/8" -14 UNF		5/8" 16	27	67,5	12,5	33,5	19,5
a	S 30 43 0 619 013 A	1"1/16 - 12 UN		1/2" 13	32	67	9,5	37,5	21,5
a	S 30 43 0 619 016 A	1"1/16 - 12 UN		5/8" 16	32	72	12,5	38	22
a	S 30 43 0 619 019 A	1"1/16 - 12 UN		3/4" 19	32	79	15	40	24
a	S 30 43 0 619 025 A	1"1/16 - 12 UN		1" 25	32	87	15	40	24
a	S 30 43 0 622 019 A	1"3/16 - 12 UN		3/4" 19	36	80,5	15	41,5	25
a	S 30 43 0 625 019 A	1"5/16 - 12 UN		3/4" 19	41	81	15	42	25
a	S 30 43 0 625 025 A	1"5/16 - 12 UN		1" 25	41	89	19,5	42	25
a	S 30 43 0 632 025 A	1"5/8 - 12 UN		1" 25	50	90,5	19,5	43,5	27
a	S 30 43 0 632 032 A	1"5/8 - 12 UN		1"1/4" 32	50	98,5	26	44	27,5
a	S 30 43 0 638 032 A	1"7/8 - 12 UN		1"1/4" 32 60		103,5	26	49	29,5
a	S 30 43 0 638 038 A	1"7/8 - 12 UN		1"1/2 38 60		107	32	49	29,5
a	S 30 43 0 650 050 A	2"1/2 - 12 UN		2" 50 75		131,5	42	59	35,5

a: dado pressato

a: crimped nut

a: aufgepresste Überwurfmutter